NSN 3120-00-003-3256

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-003-3256

Over	all I	en	ath:
~~~	an L	-611	иит.

Between 0.5610 inches and 0.5810 inches

**Body Outside Diameter:** 

Between 0.4998 inches and 0.5005 inches

**Body Inside Diameter:** 

Between 0.3758 inches and 0.3773 inches

Flange Outside Diameter:

Between 1.4900 inches and 1.5000 inches

Flange Width:

Between 0.0570 inches and 0.0670 inches

**End To Flange Distance:** 

Between 0.1090 inches and 0.1290 inches

**Corner Shape:** 

Square outside left corner

**Surface Finish:** 

80.0 microinches outside diameter surface of body

Left End Body Diameter:

Between 0.6150 inches and 0.6350 inches

**Special Features:** 

Left end flange reduced to 0.800 in. Dia, left end body 0.6150 in. Min, 0.6350 in. Maximum od, flange w of reduced area 0.035 in. Min, 0.050

in. Max

Material:

Steel

**Material Specification:** 

Mil-s-5000 military specification single material response

**Surface Treatment:** 

Cadmium

**Surface Treatment Specification:** 

114s4702-10, 77272 mfr ref single treatment response

**Style Designator:** 

Solid, external flange

**Test Data Document:** 

81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A045a0

Mil-std (military Standard):

Mil-e-5000 epac