# NSN 3120-00-003-3256

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-003-3256

# **Overall Length:**

Between 0.5610 inches and 0.5810 inches

## Body Outside Diameter:

Between 0.4998 inches and 0.5005 inches

## Body Inside Diameter:

Between 0.3758 inches and 0.3773 inches

## Flange Outside Diameter:

Between 1.4900 inches and 1.5000 inches

#### Flange Width:

Between 0.0570 inches and 0.0670 inches

# End To Flange Distance:

Between 0.1090 inches and 0.1290 inches

#### Corner Shape:

Square outside left corner

Surface Finish:

# 80.0 microinches outside diameter surface of body

# Left End Body Diameter:

Between 0.6150 inches and 0.6350 inches

# **Special Features:**

Left end flange reduced to 0.800 in. Dia, left end body 0.6150 in. Min, 0.6350 in. Maximum od, flange w of reduced area 0.035 in. Min, 0.050 in. Max

#### Material:

Steel

#### Material Specification:

Mil-s-5000 military specification single material response

#### Surface Treatment:

Cadmium

# Surface Treatment Specification:

114s4702-10, 77272 mfr ref single treatment response

# Style Designator:

Solid, external flange

# Test Data Document:

81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

```
Shelf Life:
```

N/a

## Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A045a0

Mil a E000 anaa

Mil-std (military Standard):