NSN 3120-00-004-1019

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-004-1019

Overall Length:

Between 0.5660 inches and 0.5700 inches

Body Outside Diameter:

Between 0.4374 inches and 0.4378 inches

Body Inside Diameter:

Between 0.2500 inches and 0.2505 inches

Flange Outside Diameter:

Between 0.8070 inches and 0.8170 inches

Flange Width:

Between 0.0710 inches and 0.0770 inches

Corner Shape:

Square outside right corner

Hardness Rating:

34.0 rockwell c and 38.0 rockwell c

Surface Finish:

63.0 microinches right end surface of body

Special Features:

Flange id counterbored 0.269 in. Min, 0.271 in. Maximum dia, 0.061 in. Min, 0.063 in. Maximum deep

Material:

Steel comp 630

Material Specification:

Ams5643 17-4ph assn standard single material response

Surface Treatment:

Passivate

Style Designator:

Solid, external flange one end

Test Data Document:

77272-bac5424 cl b specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0