NSN 3120-00-004-7066

Sleeve Bushing - Page 1 of 1



| view Online at https://aerobasegroup.com/nsn/3120-00-004-7066 |
|---|
| Overall Length: |
| Between 0.6520 inches and 0.6640 inches |
| Body Outside Diameter: |
| Between 1.0638 inches and 1.0648 inches |
| Body Inside Diameter: |
| Between 0.8750 inches and 0.8770 inches |
| Flange Outside Diameter: |
| 2.4400 inches |
| Flange Width: |
| Between 0.0920 inches and 0.0940 inches |
| Corner Shape: |
| Square outside right corner |
| Hardness Rating: |
| 38.0 rockwell c and 45.0 rockwell c |
| Surface Finish: |
| 125.0 microinches intermediate layer |
| Material: |
| Steel comp 630 or steel comp xm-12 |
| Material Specification: |
| Ams 5643, comp 17-4 ph assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Style Designator: |
| Solid, external flange one end |
| Test Data Document: |
| 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A045a0