NSN 3120-00-004-8896

Sleeve Bushing - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3120-00-004-8896

Overall Length:

Between 1.3050 inches and 1.3250 inches

Body Outside Diameter:

Between 0.8740 inches and 0.8745 inches

Body Inside Diameter:

Between 0.6150 inches and 0.6350 inches

Flange Outside Diameter:

Between 1.4280 inches and 1.4480 inches

Flange Width:

Between 0.1150 inches and 0.1350 inches

Interior Flange Hole Diameter:

Between 0.1810 inches and 0.2010 inches

Interior Flange Left End To Centerline Distance:

Between 0.5085 inches and 0.5585 inches

Interior Flange Width:

Between 0.4130 inches and 0.4730 inches

Corner Shape:

Square outside right corner

Surface Finish:

63.0 microinches outside diameter surface of body

Special Features:

One side of flange flat 0.575 in. To 0.627 in. From centerline of bore to flat edge

Material:

Steel

Material Specification:

Qq-s-76317-4p federal specification single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-s-5002 military specification single treatment response

Style Designator:

Solid, external flange one end, interior flang (s) not located at either end

Test Data Document:

81349-mil-i-6866 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0

NSN 3120-00-004-8896

Sleeve Bushing - Page 2 of 2



Mil-std (military Standard):

Mil-s-5002 spec.