

View Online at <https://aerobasegroup.com/nsn/3120-00-007-1506>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Shank Style:**

Externally threaded

**Overall Length:**

3.6400 inches

**Bore Diameter:**

Between 0.6245 inches and 0.6250 inches

**Outer Member Outside Diameter:**

1.5620 inches

**Bore Center To Shank End Distance:**

2.8590 inches

**Outer Member Width:**

Between 0.4950 inches and 0.5050 inches

**Inner Member Width:**

Between 0.6230 inches and 0.6250 inches

**Shank Thread Length:**

1.5780 inches

**Thread Diameter:**

0.875 inches

**Thready Qty Per Inch (tpi):**

16

**Special Features:**

Keyway in shank 0.156 in. Wide by 0.100 in. Dp and chrome on thread area

**Material:**

Steel comp 631 race insert or steel comp 630 race insert or steel comp 410 race insert

**Surface Treatment:**

Passivate rod end body

**Style Designator:**

Ball type

**Test Data Document:**

81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A045a0