

View Online at <https://aerobasegroup.com/nsn/3120-00-008-7842>

**Thread Class:**

2b

**Thread Direction:**

Left-hand

**Shank Style:**

Internally threaded w/bead and wrench flats and inspection hole

**Overall Length:**

Between 1.7500 inches and 1.7800 inches

**Bore Diameter:**

Between 0.1895 inches and 0.1915 inches

**Outer Member Outside Diameter:**

Between 0.7710 inches and 0.7910 inches

**Bore Center To Shank End Distance:**

Between 1.3650 inches and 1.3850 inches

**Outer Member Width:**

Between 0.3320 inches and 0.3420 inches

**Inner Member Width:**

Between 0.4320 inches and 0.4370 inches

**Shank Thread Length:**

Between 0.7188 inches and 0.8125 inches

**Inspection Hole Center To End Distance:**

0.3125 inches

**Shank Width Across Wrench Flats:**

0.3750 inches

**Static Radial Load Rating:**

2100 pounds

**Thread Diameter:**

0.250 inches

**Thready Qty Per Inch (tpi):**

28

**Special Features:**

Thread class may also be 3b, 4 equally spaced slots in end of shank 0.0620 in. Wide by 0.0560 in. Deep

**Material:**

Steel rod end body

**Material Specification:**

66 federal standard single material response inner member

**Surface Treatment:**

Cadmium rod end body

**Style Designator:**

Ball type

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A045a0