View Online at https://aerobasegroup.com/nsn/3120-00-008-7842

Thread Class:

2b

Thread Direction:

Left-hand

Shank Style:

Internally threaded w/bead and wrench flats and inspection hole

Overall Length:

Between 1.7500 inches and 1.7800 inches

Bore Diameter:

Between 0.1895 inches and 0.1915 inches

Outer Member Outside Diameter:

Between 0.7710 inches and 0.7910 inches

Bore Center To Shank End Distance:

Between 1.3650 inches and 1.3850 inches

Outer Member Width:

Between 0.3320 inches and 0.3420 inches

Inner Member Width:

Between 0.4320 inches and 0.4370 inches

Shank Thread Length:

Between 0.7188 inches and 0.8125 inches

Inspection Hole Center To End Distance:

0.3125 inches

Shank Width Across Wrench Flats:

0.3750 inches

Static Radial Load Rating:

2100 pounds

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

28

Special Features:

Thread class may also be 3b, 4 equally spaced slots in end of shank 0.0620 in. Wide by 0.0560 in. Deep

Material:

Steel rod end body

Material Specification:

66 federal standard single material response inner member

Surface Treatment:

Cadmium rod end body

Style Designator:

Ball type

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0