## NSN 3120-00-008-8976

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-008-8976

| Overall Length:                         |
|---|
| Between 0.5100 inches and 0.5250 inches |
| Body Outside Diameter:                  |

Between 0.4830 inches and 0.4835 inches

**Body Inside Diameter:** 

Between 0.3755 inches and 0.3760 inches

Flange Outside Diameter:

0.6800 inches

Flange Width:

Between 0.0550 inches and 0.0650 inches

**Corner Shape:** 

Square outside left corner

Surface Finish:

125.0 microinches intermediate layer

**Special Features:** 

Slot located on centerline, right surface of flange 0.2900 in. Min 0.3000 in. Maximum w, 0.0290 in. Min 0.0300 in. Maximum deep

**Surface Treatment:** 

Cadmium

**Surface Treatment Specification:** 

Qq-p-416, type 2, cl 1 federal specification single treatment response

Style Designator:

Solid, external flange one end

Test Data Document:

81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A045a0