NSN 3120-00-009-0460

Sleeve Bushing - Page 1 of 1

Demilitarization:

No Fiig: A045a0



View Online at https://aerobasegroup.com/nsn/3120-00-009-0460

| View Online at https://aerobasegroup.com/nsn/3120-00-009-0460 |
|---|
| Overall Length: |
| Between 0.4230 inches and 0.4330 inches |
| Body Outside Diameter: |
| Between 0.3755 inches and 0.3760 inches |
| Body Inside Diameter: |
| Between 0.1910 inches and 0.1925 inches |
| Flange Outside Diameter: |
| Between 0.4450 inches and 0.4500 inches |
| Flange Width: |
| Between 0.0190 inches and 0.0240 inches |
| Corner Shape: |
| Square outside right corner |
| Hardness Rating: |
| 43.0 rockwell c and 45.0 rockwell c |
| Material: |
| Steel comp xm-13 |
| Material Specification: |
| Ams 5629 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Style Designator: |
| Solid, external flange one end |
| Test Data Document: |
| 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |