

View Online at <https://aerobasegroup.com/nsn/3120-00-020-6661>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Shank Style:**

Internally threaded w/hexagon end and inspection hole

**Overall Length:**

Between 2.8250 inches and 2.8750 inches

**Bore Diameter:**

Between 0.6870 inches and 0.6875 inches

**Outer Member Outside Diameter:**

Between 1.4900 inches and 1.5100 inches

**Bore Center To Shank End Distance:**

Between 2.0800 inches and 2.1200 inches

**Outer Member Width:**

Between 0.5570 inches and 0.5670 inches

**Inner Member Width:**

Between 0.6650 inches and 0.6750 inches

**Shank Thread Length:**

1.1000 inches

**Inspection Hole Center To End Distance:**

0.5000 inches

**Shank Width Across Wrench Flats:**

0.6250 inches

**Static Radial Load Rating:**

10000 pounds

**Thread Diameter:**

0.438 inches

**Features Provided:**

Flush lubrication fitting

**Thready Qty Per Inch (tpi):**

20

**Hardness Rating:**

59.0 rockwell c inner member and 63.0 rockwell c inner member

**Material:**

Steel comp e52100 inner member

**Material Specification:**

Sae assn standard single material response rod end body

**Surface Treatment:**

Cadmium rod end body

**Style Designator:**

Ball type

**Thread Series Designator:**

Unf

**Specification Data:**

76823-14-74901b professional/industrial association specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A045a0