

View Online at <https://aerobasegroup.com/nsn/3120-00-024-5909>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Style:

Externally threaded

Overall Length:

1.9525 inches

Bore Diameter:

Between 0.1895 inches and 0.1900 inches

Outer Member Outside Diameter:

Between 0.7710 inches and 0.7910 inches

Bore Center To Shank End Distance:

Between 1.5520 inches and 1.5720 inches

Outer Member Width:

Between 0.3320 inches and 0.3420 inches

Inner Member Width:

Between 0.5550 inches and 0.5600 inches

Shank Thread Length:

Between 0.9688 inches and 1.0625 inches

Static Radial Load Rating:

2270 pounds

Thread Diameter:

0.312 inches

Thready Qty Per Inch (tpi):

24

Special Features:

Keyway in shank for standard nas 513 lockwasher

Surface Treatment:

Cadmium rod end body

Surface Treatment Specification:

Qq-p-416, type 1, cl 2 federal specification single treatment response rod end body

Style Designator:

Ball type

Test Data Document:

81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A045a0