NSN 3120-00-034-6518

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-034-6518

O,	/era	ш	l ۵n	ath	٠.
U١	/eia		Len	uu	ı.

Between 3.8650 inches and 3.8850 inches

Body Outside Diameter:

Between 10.8400 inches and 10.8600 inches

Body Inside Diameter:

Between 10.6610 inches and 10.6660 inches

Left Flange Outside Diameter:

Between 11.0250 inches and 11.0350 inches

Right Flange Outside Diameter:

Between 11.0250 inches and 11.0350 inches

Left Flange Width:

Between 0.9900 inches and 1.0100 inches

Right Flange Width:

Between 0.9900 inches and 1.0100 inches

Corner Shape:

Square right flange outside left corner

Surface Finish:

90.0 microinches intermediate layer

Material:

Steel comp e4340

Material Specification:

Mil-s-5000 military specification single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type2 class2 federal specification 1st treatment response and qq-p-416, type2 class3 federal specification 2nd treatment response

Style Designator:

Solid, external flanges both ends

Test Data Document:

81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A045a0

Mil-std (military Standard):

Mil-s-5000 spec.