## NSN 3120-00-043-0992



Sleeve Bushing - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/3120-00-043-0992 Slot Width: 0.0230 inches first and 0.0350 inches first Slot Length: 0.1840 inches first and 0.1970 inches first **Overall Length:** Between 0.9130 inches and 0.9350 inches **Body Outside Diameter:** Between 1.3765 inches and 1.3770 inches **Body Inside Diameter:** Between 1.1255 inches and 1.1260 inches Flange Outside Diameter: Between 1.5400 inches and 1.5530 inches Flange Width: Between 0.0950 inches and 0.1050 inches

**End To Flange Distance:** 

Between 0.1900 inches and 0.1980 inches

**Corner Shape:** 

Square outside left corner

Hardness Rating:

149.0 brinell hultgren and 255.0 brinell hultgren

Surface Finish:

63.0 microinches right end surface of flange

**Antirotation/lubrication Type And Quantity:** 

4 slot

Left End Body Diameter:

Between 1.3765 inches and 1.3770 inches

**Right End Body Diameter:** 

Between 1.3765 inches and 1.3770 inches

Material:

Copper alloy

**Style Designator:** 

Solid, external flange

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A045a0