## NSN 3120-00-050-6319

**Demilitarization:** 

No Fiig: A045a0



Sleeve Bushing - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/3120-00-050-6319 **Overall Length:** Between 2.4430 inches and 2.4730 inches **Body Outside Diameter:** Between 0.8714 inches and 0.8721 inches **Body Inside Diameter:** Between 0.6900 inches and 0.6950 inches Flange Outside Diameter: Between 1.2100 inches and 1.2300 inches Flange Width: Between 0.3000 inches and 0.3200 inches **Corner Shape:** Square outside left corner **Criticality Code Justification:** Feat **Surface Finish:** 63.0 microinches right end surface of body **Special Features:** Id of end opposite flange taperedfrom 0.6900 in. Min, 0.6950 in. Maximum to 0.5020 in. Min, 0.5050 in. Max, 0.6300 in. Nom Ig, round inside corner where taper and id meet 0.0200 in. Min, 0.0400 in. Maximum radius Material: Steel comp 630 **Material Specification:** Ams 5643 assn standard single material response **Surface Treatment:** Cadmium right end surface of left flange and chromate right end surface of left flange **Surface Treatment Specification:** Qq-p-416 type 2 class 3 federal specification single treatment response right end surface of left flange Style Designator: Solid, external flange one end Shelf Life: N/a **Unit Of Measure:**