# NSN 3120-00-050-6320

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-050-6320

Over	all I	en	ath:
~~~	an L	-611	иит.

Between 1.8180 inches and 1.8480 inches

**Body Outside Diameter:** 

Between 0.8714 inches and 0.8721 inches

**Body Inside Diameter:** 

Between 0.6900 inches and 0.6950 inches

Flange Outside Diameter:

Between 1.2100 inches and 1.2300 inches

Flange Width:

Between 0.3000 inches and 0.3200 inches

**Corner Shape:** 

Square outside left corner

Surface Finish:

63.0 microinches right end surface of body

#### **Special Features:**

I/d of end opposite flange, tapered from 0.6900 in. Min, 0.6950 in. Maximum to 0.5020 in. Min, 0.5050 in. Max, 0.5900 in. Min, 0.6100 in.

Maximum length, round inside corner where taper and i/d meet 0.0200 in. Min, 0.0400 in. Maximum radius

Material:

Steel comp 630

#### **Material Specification:**

Ams 5643 assn standard single material response

## **Surface Treatment:**

Cadmium right end surface of left flange or cadmium right end surface of left flange and chromate right end surface of left flange or cadmium right end surface of left flange and phosphate right end surface of left flange

### **Surface Treatment Specification:**

Qq-p-416 federal specification single treatment response right end surface of left flange

### **Style Designator:**

Solid, external flange one end

Shelf Life:

N/a

Unit Of Measure:

\_

Demilitarization:

No

Fiig:

A045a0