NSN 3120-00-055-9599

Sleeve Bushing - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3120-00-055-9599

Slot Width:

0.0200 inches first and 0.0400 inches first

Slot Length:

0.1720 inches first and 0.2030 inches first

Overall Length:

Between 0.6620 inches and 0.7040 inches

Body Outside Diameter:

Between 2.2230 inches and 2.2240 inches

Body Inside Diameter:

Between 2.0472 inches and 2.0478 inches

Flange Outside Diameter:

Between 4.0600 inches and 4.1200 inches

Flange Width:

Between 0.0800 inches and 0.1000 inches

Right Internal Flange Hole Diameter:

Between 1.8300 inches and 1.8500 inches

Right Internal Flange Width:

Between 0.0800 inches and 0.1000 inches

End To Flange Distance:

0.0500 inches

Corner Shape:

Square inside left corner

Features Provided:

Casehardened

Hardness Rating:

79.0 rockwell a and 85.0 rockwell a

Antirotation/lubrication Type And Quantity:

3 slot

Left End Body Diameter:

Between 2.2230 inches and 2.2240 inches

Right End Body Diameter:

Between 2.2230 inches and 2.2240 inches

Special Features:

Two holes 0.260 to 0.265 in. Diameter spaced 105 degrees apart on 1.620 in. Radius, two holes 0.120 to 0.130 in. Diameter equally spaced 0.285 in. Perpendicular to radius of other bolt circle within the arc, fan shaped end view one half on 1.470 to 1.500 in. Radius extending2.030 to 2.060 in. Radius to form fan

Material:

Steel

Style Designator:

Solid, external flange, internal flange one end

Shelf Life:

N/a

- Unit Of Measure:
- --

NSN 3120-00-055-9599

Sleeve Bushing - Page 2 of 2

Demilitarization:

No

Fiig:

A045a0

