

View Online at <https://aerobasegroup.com/nsn/3120-00-056-3380>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Style:

Externally threaded

Overall Length:

1.2785 inches

Bore Diameter:

Between 0.1895 inches and 0.1915 inches

Outer Member Outside Diameter:

Between 0.5520 inches and 0.5620 inches

Bore Center To Shank End Distance:

Between 0.9690 inches and 1.0310 inches

Outer Member Width:

Between 0.1770 inches and 0.1970 inches

Inner Member Width:

Between 0.2450 inches and 0.2500 inches

Shank Thread Length:

0.5930 inches

Static Radial Load Rating:

1430 pounds

Thread Diameter:

0.250 inches

Features Provided:

Flush lubrication fitting

Thready Qty Per Inch (tpi):

28

Lubrication Feature:

Perforation inner member

Special Features:

Radial clearance 0.0005 in. Tir; keyway in shank for nas559 or nas513 lockwasher

Material:

Steel comp e52100 inner member

Material Specification:

Sae assn standard single material response rod end body

Surface Treatment:

Cadmium rod end body

Style Designator:

Ball type

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0