# NSN 3120-00-056-4320

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-056-4320

Overa	II Le	ngth:

Between 0.7240 inches and 0.7440 inches

## **Body Inside Diameter:**

Between 0.5007 inches and 0.5027 inches

## Flange Outside Diameter:

Between 0.8650 inches and 0.8850 inches

## Flange Width:

Between 0.0570 inches and 0.0670 inches

## **End To Flange Distance:**

Between 0.0970 inches and 0.1270 inches

#### **Corner Shape:**

Square outside left corner

## Surface Finish:

80.0 microinches outside diameter surface of body

## Left End Body Diameter:

Between 0.7400 inches and 0.7600 inches

## **Right End Body Diameter:**

Between 0.7400 inches and 0.7600 inches

## **Special Features:**

O/d on right end 0.6257 in. Min, 0.6265 in. Max

## Material:

Steel comp e4340

# **Material Specification:**

Mil-s-5000 military specification single material response

## **Surface Treatment:**

Cadmium

## **Surface Treatment Specification:**

Qq-p-416, type 1, cl 1 federal specification single treatment response

## **Style Designator:**

Solid, external flange

## Shelf Life:

N/a

## **Unit Of Measure:**

## **Demilitarization:**

No

# Fiig:

A045a0

## Mil-std (military Standard):

Mil-s-5000 spec.