

View Online at <https://aerobasegroup.com/nsn/3120-00-064-5264>

Thread Class:

3b

Thread Direction:

Left-hand

Shank Style:

Internally threaded w/bead and wrench flats and inspection hole

Overall Length:

1.7810 inches

Bore Diameter:

Between 0.1895 inches and 0.1900 inches

Lubrication Material:

Lubricant, dry film

Outer Member Outside Diameter:

Between 0.7450 inches and 0.7500 inches

Bore Center To Shank End Distance:

Between 1.3430 inches and 1.4680 inches

Outer Member Width:

Between 0.3230 inches and 0.3280 inches

Inner Member Width:

Between 0.4320 inches and 0.4370 inches

Shank Thread Length:

0.7500 inches

Inspection Hole Center To End Distance:

0.2500 inches

Shank Width Across Wrench Flats:

0.3750 inches

Static Radial Load Rating:

6780 pounds

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

28

Hardness Rating:

59.0 rockwell c inner member

Lubrication Feature:

Groove internal outer member

Special Features:

Magnetic inspection required

Material:

Steel comp 630 rod end body

Surface Treatment:

Chromium inner member

Style Designator:

Ball type

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A045a0