

View Online at <https://aerobasegroup.com/nsn/3120-00-067-7643>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Shank Style:**

Internally threaded w/inspection hole

**Overall Length:**

3.2500 inches

**Bore Diameter:**

Between 0.6245 inches and 0.6265 inches

**Lubrication Material:**

Lubricating oil

**Outer Member Outside Diameter:**

Between 1.4900 inches and 1.5100 inches

**Bore Center To Shank End Distance:**

Between 2.4850 inches and 2.5150 inches

**Outer Member Width:**

Between 0.5570 inches and 0.5670 inches

**Inner Member Width:**

Between 0.7450 inches and 0.7500 inches

**Shank End To Shoulder Length:**

Between 1.7400 inches and 1.7600 inches

**Shank Thread Length:**

1.5000 inches

**Inspection Hole Center To End Distance:**

0.7500 inches

**Static Radial Load Rating:**

7000 pounds

**Thread Diameter:**

0.625 inches

**Features Provided:**

External lubrication fitting

**Thready Qty Per Inch (tpi):**

18

**Lubrication Feature:**

Groove internal outer member

**Material:**

Steel rod end body

**Material Specification:**

-ams 7440 assn standard single material response rod end body

**Surface Treatment:**

Cadmium

**Style Designator:**

Shouldered ball type

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A045a0