NSN 3120-00-068-7527

Mil-s-5626 spec.



Sleeve Bushing - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/3120-00-068-7527 **Hole Diameter:** 0.1080 inches first and 0.1140 inches first **Overall Length:** Between 0.8140 inches and 0.8440 inches **Body Outside Diameter:** Between 2.8740 inches and 2.8750 inches **Body Inside Diameter:** Between 2.6510 inches and 2.6560 inches Flange Outside Diameter: Between 3.0500 inches and 3.0700 inches Flange Width: Between 0.0800 inches and 0.0900 inches **Corner Shape:** Square left flange outside right corner **Surface Finish:** 63.0 microinches intermediate layer **Antirotation/lubrication Type And Quantity:** 2 hole **Special Features:** Holes drilled on a 60.0 degrees angle Material: Steel comp 4140 or steel comp 4130 **Material Specification:** Ams 6381 assn standard 1st material response or mil-s-5626 com+4140 cond c4 military specification 2nd material response or mil-s-6758 cond d1 military specification 3rd material response **Style Designator:** Solid, external flange one end Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: A045a0 Mil-std (military Standard):