

View Online at <https://aerobasegroup.com/nsn/3120-00-087-9679>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Style:

Externally threaded

Overall Length:

Between 1.9325 inches and 1.9425 inches

Bore Diameter:

Between 0.2495 inches and 0.2515 inches

Lubrication Material:

Lubricant, manufacturers standard

Outer Member Outside Diameter:

Between 0.7400 inches and 0.7600 inches

Bore Center To Shank End Distance:

1.5625 inches

Outer Member Width:

Between 0.2760 inches and 0.2860 inches

Inner Member Width:

Between 0.3700 inches and 0.3750 inches

Shank Thread Length:

Between 0.9688 inches and 1.0625 inches

Static Radial Load Rating:

1950 pounds

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

28

Hardness Rating:

60.0 rockwell c inner member and 63.0 rockwell c inner member

Lubrication Feature:

Groove internal outer member

Material:

Steel rod end body

Surface Treatment:

Cadmium rod end body

Surface Treatment Specification:

Qq-p-416, t1, cl1 federal specification single treatment response rod end body

Style Designator:

Ball type

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0