NSN 3120-00-089-9716

Sleeve Bushing - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/3120-00-089-9716 |
|--|
| Overall Length: |
| Between 0.2620 inches and 0.2770 inches |
| Body Outside Diameter: |
| Between 0.5631 inches and 0.5638 inches |
| Body Inside Diameter: |
| Between 0.4375 inches and 0.4390 inches |
| Flange Outside Diameter: |
| Between 0.6770 inches and 0.6970 inches |
| Flange Width: |
| Between 0.0570 inches and 0.0620 inches |
| Corner Shape: |
| Undercut left flange body corner |
| Surface Finish: |
| 100.0 microinches intermediate layer |
| Special Features: |
| ld and od to be parallel and concentric within 0.0030 tir |
| Material: |
| Steel comp 4130 or steel comp 8630 |
| Material Specification: |
| Mil-s-6758 military specification 1st material response or mil-s-6050 military specification 2nd material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Qq-p-416, type 2, cl 3 federal specification single treatment response |
| Style Designator: |
| Solid, external flange one end |
| Specification Data: |
| 80205-nas77 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A045a0 |

Mil-s-6758 spec.

Mil-std (military Standard):