## NSN 3120-00-099-5708

Sleeve Bearing Half - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3120-00-099-5708

**Hole Diameter:** 0.1250 inches first **Overall Length:** Between 0.7790 inches and 0.7890 inches **Body Outside Diameter:** 2.1250 inches **Body Inside Diameter:** Between 1.9700 inches and 1.9710 inches **Distance From Centerline Of Opening To Left End Of Bearing:** 0.3820 inches first and 0.4020 inches first **Locking Lug Height:** Between 0.0310 inches and 0.0410 inches **Locking Lug Length:** Between 0.1900 inches and 0.2200 inches **Locking Lug Width:** Between 0.1500 inches and 0.1550 inches **Corner Shape:** Square all corners **Antirotation/lubrication Type And Quantity:** 1 hole **Distance From Lug End To End Of Bearing:** Between 0.2025 inches and 0.2075 inches **Special Features:** Pkg of 8 ea atac part no. 7345263 bearing half sleeve Material: Steel outer layer **Material Specification:** Sae 485 assn standard single material response inner layer **Surface Treatment:** Lead alloy inside diameter surface of body **Surface Treatment Specification:** Mil-b-13506, comp 19 military specification single treatment response inside diameter surface of body **Style Designator:** Half sleeve, plain, no outside flanges Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig: A045a0

## NSN 3120-00-099-5708

Sleeve Bearing Half - Page 2 of 2



Mil-std (military Standard):

Mil-b-13506 spec.