## NSN 3120-00-103-6681

Sleeve Bushing - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3120-00-103-6681

**Hole Diameter:** 

0.5520 inches first and 0.5720 inches first

**Overall Length:** 

2.1000 inches

**Body Outside Diameter:** 

Between 1.8040 inches and 1.8050 inches

**Body Inside Diameter:** 

Between 1.5900 inches and 1.6100 inches

Flange Outside Diameter:

Between 2.6200 inches and 2.6400 inches

Flange Width:

Between 0.1000 inches and 0.1200 inches

**Right Internal Flange Hole Diameter:** 

Between 1.4300 inches and 1.4500 inches

**Right Internal Flange Width:** 

Between 0.1700 inches and 0.1900 inches

**Corner Shape:** 

Square outside right corner

**Hardness Rating:** 

39.0 rockwell c and 42.0 rockwell c

Surface Finish:

125.0 microinches intermediate layer

**Antirotation/lubrication Type And Quantity:** 

4 hole

**Special Features:** 

4 mounting holes on flange0.2200 in min, 0.2270 in maximum diameter on 2.2180 in bolt circle dia

Material:

Steel comp 4340

Material Specification:

Ams 6415 assn standard single material response

**Surface Treatment:** 

Tin and cadmium

**Surface Treatment Specification:** 

Kps537 cl 1, fsc-84955 mfr ref single treatment response outside diameter surface of body

**Style Designator:** 

Solid, external flange one end, internal flange one end

**Test Data Document:** 

84955-arps208 ratingd specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

**Unit Of Measure:** 

--

## NSN 3120-00-103-6681

Sleeve Bushing - Page 2 of 2



Demilitarization:

No

Fiig:

A045a0