NSN 3120-00-103-6681

Sleeve Bushing - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3120-00-103-6681

Hole Diameter:

0.5520 inches first and 0.5720 inches first

Overall Length:

2.1000 inches

Body Outside Diameter:

Between 1.8040 inches and 1.8050 inches

Body Inside Diameter:

Between 1.5900 inches and 1.6100 inches

Flange Outside Diameter:

Between 2.6200 inches and 2.6400 inches

Flange Width:

Between 0.1000 inches and 0.1200 inches

Right Internal Flange Hole Diameter:

Between 1.4300 inches and 1.4500 inches

Right Internal Flange Width:

Between 0.1700 inches and 0.1900 inches

Corner Shape:

Square outside right corner

Hardness Rating:

39.0 rockwell c and 42.0 rockwell c

Surface Finish:

125.0 microinches intermediate layer

Antirotation/lubrication Type And Quantity:

4 hole

Special Features:

4 mounting holes on flange0.2200 in min, 0.2270 in maximum diameter on 2.2180 in bolt circle dia

Material:

Steel comp 4340

Material Specification:

Ams 6415 assn standard single material response

Surface Treatment:

Tin and cadmium

Surface Treatment Specification:

Kps537 cl 1, fsc-84955 mfr ref single treatment response outside diameter surface of body

Style Designator:

Solid, external flange one end, internal flange one end

Test Data Document:

84955-arps208 ratingd specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

NSN 3120-00-103-6681

Sleeve Bushing - Page 2 of 2



Demilitarization:

No

Fiig:

A045a0