

View Online at <https://aerobasegroup.com/nsn/3120-00-104-4666>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Style:

Externally threaded

Overall Length:

Between 8.9100 inches and 8.9900 inches

Bore Diameter:

Between 0.4995 inches and 0.5000 inches

Outer Member Outside Diameter:

Between 1.5700 inches and 1.6300 inches

Bore Center To Shank End Distance:

Between 8.1400 inches and 8.1600 inches

Outer Member Width:

Between 0.3850 inches and 0.3950 inches

Inner Member Width:

Between 0.4980 inches and 0.5000 inches

Shank Thread Length:

Between 6.4900 inches and 6.5100 inches

Static Radial Load Rating:

21000 pounds

Thread Diameter:

0.875 inches

Thready Qty Per Inch (tpi):

14

Hardness Rating:

26.0 rockwell c rod end body and 33.0 rockwell c rod end body

Material:

Steel rod end body

Material Specification:

Mil-s-6758 military specification single material response rod end body

Surface Treatment:

Chromium inner member

Surface Treatment Specification:

Qq-c-320 federal specification single treatment response inner member

Style Designator:

Ball type

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0

Mil-std (military Standard):

Mil-s-6758 spec.