NSN 3120-00-106-4329

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-106-4329
Overall Length:
Between 1.7900 inches and 1.8000 inches
Body Outside Diameter:
Between 1.3160 inches and 1.3200 inches
Body Inside Diameter:
Between 1.1250 inches and 1.1270 inches
Flange Outside Diameter:
2.0000 inches
Flange Width:
Between 0.2300 inches and 0.2400 inches
Corner Shape:
Undercut left flange body corner
Hardness Rating:
34.0 rockwell c and 39.0 rockwell c
Surface Finish:
125.0 microinches intermediate layer
Special Features:
Counterbore, 1.7600 in. Min, 1.7700 in.Max, dia, 0.0600 in. Min, 0.0700 in. Max, deep, located on flange face
Material:
Steel comp 4130
Material Specification:
Mil-s-6758, comp 4130 military specification single material response
Surface Treatment:
Cadmium or chromium
Surface Treatment Specification:
Cpt 8204, 13002 mfr ref 1st treatment response or cpt 8205, 13002 mfr ref 2nd treatment response
Style Designator:
Solid, external flange one end
Test Data Document:
81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

Mil-std (military Standard):

Mil-s-6758 spec.

A045a0