

View Online at <https://aerobasegroup.com/nsn/3120-00-106-8642>

Thread Class:

3b

Thread Direction:

Right-hand

Shank Style:

Internally threaded w/bead and wrench flats and inspection hole

Overall Length:

1.2810 inches

Bore Diameter:

Between 0.1900 inches and 0.1915 inches

Lubrication Material:

Grease, mil-g-23827

Outer Member Outside Diameter:

0.5620 inches

Bore Center To Shank End Distance:

Between 0.9687 inches and 1.0312 inches

Outer Member Width:

Between 0.1770 inches and 0.1970 inches

Inner Member Width:

Between 0.2450 inches and 0.2500 inches

Shank Thread Length:

0.5000 inches

Inspection Hole Center To End Distance:

Between 0.2500 inches and 0.3125 inches

Shank Width Across Wrench Flats:

0.2810 inches

Static Radial Load Rating:

2100 pounds

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Lubrication Feature:

Groove race insert

Material:

Steel comp e52100 inner member

Material Specification:

Fed standard 66 federal standard single material response rod end body

Surface Treatment:

Cadmium rod end body

Style Designator:

Ball type

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0