

View Online at <https://aerobasegroup.com/nsn/3120-00-107-1149>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Style:

Externally threaded

Overall Length:

3.9500 inches

Bore Diameter:

Between 0.4995 inches and 0.5000 inches

Outer Member Outside Diameter:

1.5000 inches

Bore Center To Shank End Distance:

3.2000 inches

Outer Member Width:

Between 0.5000 inches and 0.5100 inches

Inner Member Width:

Between 0.6230 inches and 0.6250 inches

Shank Thread Length:

1.9500 inches

Thread Diameter:

0.500 inches

Thready Qty Per Inch (tpi):

20

Material:

Steel comp 630 or steel comp 631 race insert

Material Specification:

Ams5643 assn standard 1st material response or ams 5528 or aisi 410, fscm 73428 assn standard 2nd material response race insert

Surface Treatment:

Cadmium and chromate rod end body

Surface Treatment Specification:

Mil-c-8837, type 2, class 1 military specification all treatment responses rod end body

Style Designator:

Ball type

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A045a0

Mil-std (military Standard):

Mil-s-5000 spec.