# NSN 3120-00-110-2837

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-110-2837

# **Overall Length:**

Between 1.1600 inches and 1.1800 inches

#### **Body Outside Diameter:**

Between 2.2470 inches and 2.2490 inches

# **Body Inside Diameter:**

Between 2.1040 inches and 2.1060 inches

#### Left Flange Outside Diameter:

Between 2.8400 inches and 2.8800 inches

#### **Right Flange Outside Diameter:**

Between 2.3980 inches and 2.4000 inches

#### Left Flange Width:

0.4010 inches

Right Flange Width:

Between 0.0800 inches and 0.1000 inches

#### **Corner Shape:**

Square right flange outside left corner

#### Surface Finish:

63.0 microinches outside diameter surface of right flange

# **Special Features:**

Od surf. Radius porm 0.005 to 0.015 in. To flanges; from od surf. Porm 0.136 to 0.142 in. Raise to diameter of small flange 0.15 in. And .035 in. R to large flange; large flange 1/2 porm 1.42 to 1.44 r; other 1/2 rectangular opposite sides flush w radius; flat side porm 1.28 to 1.30 in. From center of bore; also 2holes porm 0.233 to 0.239 diameter on 1.5052 in. Bc 2.25 in. Apart; large flange is largest od flange

# Material:

Steel

# **Material Specification:**

Ams 5645 assn standard single material response

# Style Designator:

Solid, external flanges both ends

Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

#### Fiig:

A045a0