NSN 3120-00-121-6666

Sleeve Bushing - Page 1 of 1



| view Online at https://aerobasegroup.com/nsn/3120-00-121-0000 |
|---|
| Overall Length: |
| Between 0.3750 inches and 0.3800 inches |
| Body Outside Diameter: |
| Between 0.3740 inches and 0.3750 inches |
| Body Inside Diameter: |
| Between 0.2497 inches and 0.2507 inches |
| Flange Outside Diameter: |
| Between 0.5520 inches and 0.5720 inches |
| Flange Width: |
| Between 0.1040 inches and 0.1090 inches |
| Corner Shape: |
| Square outside right corner |
| Hardness Rating: |
| 33.0 rockwell c and 37.0 rockwell c |
| Surface Finish: |
| 125.0 microinches intermediate layer |
| Special Features: |
| ld at flange end countersunk 0.4970 in. Min, 0.5170 in. Maximum diameter by 99.5 min, 100.5 maximum degrees angle |
| Material: |
| Steel comp 4130 |
| Material Specification: |
| Mil-s-6758 military specification single material response |
| Style Designator: |
| Solid, external flange one end |
| Test Data Document: |
| 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A045a0

Mil-std (military Standard):

Mil-s-6758 spec.