NSN 3120-00-127-2442

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-127-2442
Overall Length:
Between 3.5310 inches and 3.5510 inches
Body Outside Diameter:
Between 1.1271 inches and 1.1281 inches
Body Inside Diameter:
Between 0.8370 inches and 0.8420 inches
Flange Outside Diameter:
Between 1.3070 inches and 1.3170 inches
Flange Width:
Between 0.0880 inches and 0.0920 inches
Corner Shape:
Square outside right corner
Surface Finish:
63.0 microinches right end surface of body
Special Features:
ld, counterbored on flanged end 0.9670 in. Min, 0.9720 in. Maximum diameter to 2.6150 in. Min, 2.6350 in. Maximum lg with a 0.2200 in.
Min, 0.2800 in. Maximum end radius
Material:
Steel comp 4130 or steel comp 4140
Material Specification:
Mil-s-6758 sae4130 military specification 1st material response or mil-t-6736, comp 4130, type 1, cond n military specification 2nd material
response or mil-s-5626 military specification 3rd material response or ams 6381 military specification 4th material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
204-947-002, fscm 97499 mfr ref single treatment response
Style Designator:
Solid, external flange one end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A045a0

Mil-s-6758 spec.

Mil-std (military Standard):