NSN 3120-00-127-2442

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-127-2442

Overall Length:

Between 3.5310 inches and 3.5510 inches

Body Outside Diameter:

Between 1.1271 inches and 1.1281 inches

Body Inside Diameter:

Between 0.8370 inches and 0.8420 inches

Flange Outside Diameter:

Between 1.3070 inches and 1.3170 inches

Flange Width:

Between 0.0880 inches and 0.0920 inches

Corner Shape:

Square outside right corner

Surface Finish:

63.0 microinches right end surface of body

Special Features:

Id, counterbored on flanged end 0.9670 in. Min, 0.9720 in. Maximum diameter to 2.6150 in. Min, 2.6350 in. Maximum Ig with a 0.2200 in.

Min, 0.2800 in. Maximum end radius

Material:

Steel comp 4130 or steel comp 4140

Material Specification:

Mil-s-6758 sae4130 military specification 1st material response or mil-t-6736, comp 4130, type 1, cond n military specification 2nd material response or mil-s-5626 military specification 3rd material response or ams 6381 military specification 4th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

204-947-002, fscm 97499 mfr ref single treatment response

Style Designator:

Solid, external flange one end

Shelf Life:

N/a

Unit Of Measure:

```
---
```

Demilitarization:

No

Fiig:

A045a0

Mil-std (military Standard):

Mil-s-6758 spec.