

View Online at <https://aerobasegroup.com/nsn/3120-00-128-1952>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Shank Style:**

Externally threaded

**Overall Length:**

3.5000 inches

**Bore Diameter:**

Between 0.3745 inches and 0.3750 inches

**Outer Member Outside Diameter:**

Between 0.9900 inches and 1.0100 inches

**Bore Center To Shank End Distance:**

Between 2.9900 inches and 3.0100 inches

**Outer Member Width:**

Between 0.4010 inches and 0.4110 inches

**Inner Member Width:**

Between 0.4950 inches and 0.5000 inches

**Shank Thread Length:**

2.2500 inches

**Static Radial Load Rating:**

10380 pounds

**Thread Diameter:**

0.500 inches

**Thready Qty Per Inch (tpi):**

20

**Hardness Rating:**

56.0 rockwell c inner member

**Material:**

Steel comp 630 rod end body

**Style Designator:**

Ball type

**Test Data Document:**

81349-mil-i-6866 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

**Fiig:**

A045a0