

View Online at <https://aerobasegroup.com/nsn/3120-00-133-6463>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Style:

Externally threaded

Overall Length:

Between 1.6400 inches and 1.6650 inches

Bore Diameter:

Between 0.2495 inches and 0.2500 inches

Outer Member Outside Diameter:

Between 0.7400 inches and 0.7500 inches

Bore Center To Shank End Distance:

Between 1.2700 inches and 1.2900 inches

Outer Member Width:

Between 0.2760 inches and 0.2860 inches

Inner Member Width:

Between 0.3700 inches and 0.3750 inches

Shank Thread Length:

0.7200 inches

Static Radial Load Rating:

3620 pounds

Thread Diameter:

0.312 inches

Thready Qty Per Inch (tpi):

24

Special Features:

Dry film lubrication on spherical surface of race, 13.0 degrees approx misalignment

Material:

Steel rod end body

Material Specification:

Fefed standard 66 federal specification single material response inner member

Surface Treatment:

Cadmium rod end body

Surface Treatment Specification:

97499209-001-021-1 mfr ref single treatment response rod end body

Style Designator:

Ball type

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A045a0