

View Online at <https://aerobasegroup.com/nsn/3120-00-133-6525>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Shank Style:**

Externally threaded

**Overall Length:**

Between 1.9270 inches and 1.9470 inches

**Bore Diameter:**

Between 0.2500 inches and 0.2515 inches

**Lubrication Material:**

Grease

**Outer Member Outside Diameter:**

Between 0.7400 inches and 0.7600 inches

**Bore Center To Shank End Distance:**

Between 1.5520 inches and 1.5720 inches

**Outer Member Width:**

Between 0.2760 inches and 0.2860 inches

**Inner Member Width:**

Between 0.3700 inches and 0.3750 inches

**Shank Thread Length:**

1.0000 inches

**Static Radial Load Rating:**

1695 pounds

**Thread Diameter:**

0.250 inches

**Thready Qty Per Inch (tpi):**

28

**Hardness Rating:**

60.0 rockwell c inner member

**Lubrication Feature:**

Groove race insert

**Special Features:**

Tight internal fit

**Material:**

Steel rod end body

**Material Specification:**

Ams 7440 assn standard single material response inner member

**Surface Treatment:**

Cadmium rod end body

**Surface Treatment Specification:**

Qq-p-416, type 1, cl 2 federal specification single treatment response rod end body

**Style Designator:**

Ball type

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A045a0