# NSN 3120-00-133-6611

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-133-6611

# **Overall Length:**

Between 0.2930 inches and 0.3030 inches

## Body Outside Diameter:

Between 0.3756 inches and 0.3761 inches

# **Body Inside Diameter:**

Between 0.2380 inches and 0.2430 inches

#### Flange Outside Diameter:

Between 0.4900 inches and 0.5100 inches

#### Flange Width:

Between 0.0880 inches and 0.0930 inches

#### Corner Shape:

Undercut left flange body corner

#### Hardness Rating:

26.0 rockwell c and 33.0 rockwell c

#### Surface Finish:

125.0 microinches intermediate layer

## Material:

Steel comp 4130

## **Material Specification:**

Mil-s-6758 military specification single material response

# Surface Treatment:

Cadmium and chromate or cadmium and phosphate

## Surface Treatment Specification:

Qq-p-416, ty2 or 3 cl2 federal specification single treatment response

## Style Designator:

Solid, external flange one end

## **Test Data Document:**

81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Shelf Life:

N/a

# Unit Of Measure:

```
--
```

#### Demilitarization:

No

Fiig:

A045a0

Mil-std (military Standard):

Mil-s-6758 spec.