# NSN 3120-00-136-0996

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-136-0996

# **Overall Length:**

Between 0.2760 inches and 0.2810 inches

# **Body Outside Diameter:**

Between 0.2120 inches and 0.2150 inches

# **Body Inside Diameter:**

Between 0.1810 inches and 0.1820 inches

# Flange Outside Diameter:

Between 0.3500 inches and 0.3550 inches

#### Flange Width:

Between 0.0290 inches and 0.0330 inches

# Corner Shape:

Square outside right corner

# **Features Provided:**

Casehardened

#### Hardness Rating:

45.0 rockwell c and 85.0 rockwell c

# Material:

Copper alloy 172

# **Material Specification:**

Qq-c-530 federal specification single material response

# Surface Treatment:

Copper and nickel

# Surface Treatment Specification:

Mil-c-14550, cl 4 military specification 1st treatment response and mil-c-26074, cl 2 military specification 2nd treatment response

# Style Designator:

Solid, external flange one end

# **Test Data Document:**

98230-on124530 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

# Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

# Fiig:

A045a0

# Mil-std (military Standard):

Mil-c-14550 spec.