NSN 3120-00-149-8929

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-149-8929

Over	all I	en	ath:
~~~	an L	-611	иит.

Between 0.8480 inches and 0.8730 inches

## **Body Outside Diameter:**

Between 1.2495 inches and 1.2499 inches

## **Body Inside Diameter:**

Between 1.1024 inches and 1.1028 inches

## Flange Outside Diameter:

Between 1.4200 inches and 1.4300 inches

## Flange Width:

Between 0.1080 inches and 0.1130 inches

## **Right Internal Flange Hole Diameter:**

Between 0.9400 inches and 0.9600 inches

## **Right Internal Flange Width:**

Between 0.0680 inches and 0.0830 inches

#### **Corner Shape:**

Square outside right corner

#### **Surface Finish:**

250.0 microinches right end surface of body

## **Special Features:**

Drilled hole in flange 0.096 in. Min, 0.106 in. Maximum dia, 0.080 in. Min, 0.110 in. Max, deep, on c/l, 0.630 in. From horizontal c/l, one groove 76 degrees min, 78 degrees max, from drilled hole

## Material:

Aluminum alloy 6061

## **Material Specification:**

Qq-a-225/8 federal specification single material response

## **Surface Treatment:**

Anodize

## **Surface Treatment Specification:**

Ems-52401, type 1, cl c, 99193 mfr ref single treatment response

### **Style Designator:**

Solid, external flange one end, internal flange one end

## Shelf Life:

N/a

## **Unit Of Measure:**

Demilitarization:

No

## Fiig:

A045a0