

View Online at <https://aerobasegroup.com/nsn/3120-00-151-5025>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Style:

Externally threaded

Overall Length:

Between 3.1150 inches and 3.1350 inches

Bore Diameter:

Between 0.7497 inches and 0.7502 inches

Lubrication Material:

Grease

Outer Member Outside Diameter:

Between 1.7400 inches and 1.7600 inches

Bore Center To Shank End Distance:

2.2500 inches

Outer Member Width:

Between 0.6450 inches and 0.6550 inches

Inner Member Width:

Between 0.8700 inches and 0.8750 inches

Shank Thread Length:

0.8720 inches

Thread Diameter:

0.8120 inches

Features Provided:

External lubrication fitting

Thready Qty Per Inch (tpi):

20

Hardness Rating:

55.0 rockwell c inner member and 60.0 rockwell c inner member

Lubrication Feature:

Perforation outer race member

Special Features:

Beryllium copper flanged bushing installed in id. Of ball; nylon locking insert in threaded body near shoulder

Material:

Steel comp xm-13 rod end body

Style Designator:

Ball type

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0