NSN 3120-00-151-5096

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-151-5096

| Overall Langth: |
|---|
| Overall Length: |
| 1.1280 inches |
| Body Outside Diameter: |
| Between 1.9370 inches and 1.9380 inches |
| Body Inside Diameter: |
| Between 1.7350 inches and 1.7380 inches |
| Flange Outside Diameter: |
| 2.3750 inches |
| Flange Width: |
| Between 0.0880 inches and 0.0930 inches |
| Corner Shape: |
| Square outside right corner |
| Hardness Rating: |
| 39.0 rockwell c and 42.0 rockwell c |
| Surface Finish: |
| 125.0 microinches intermediate layer |
| Material: |
| Steel comp 4340 |
| Material Specification: |
| Mil-s-8844 military specification single material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Qq-p-416 cl2ty2 federal specification single treatment response |
| Style Designator: |
| Solid, external flange one end |
| Test Data Document: |
| 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A045a0 |
| Mil-std (military Standard): |
| Mil-s-8844 spec. |