NSN 3120-00-171-2232

Sleeve Bearing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-171-2232

		_				
Ho	ΙΔ.	n	i o r	ne	5 †4	ar.
110	16	$\boldsymbol{\omega}$	ıaı	115	7 L.	≂ı .

0.6830 inches first and 0.6940 inches first

Overall Length:

Between 0.9940 inches and 1.0000 inches

Body Outside Diameter:

Between 1.8400 inches and 1.8450 inches

Body Inside Diameter:

Between 1.6700 inches and 1.6900 inches

Left Internal Flange Hole Diameter:

Between 1.3600 inches and 1.3800 inches

Left Internal Flange Width:

Between 0.1000 inches and 0.1100 inches

Corner Shape:

Square all corners

Hardness Rating:

34.0 rockwell c and 38.0 rockwell c

Surface Finish:

125.0 microinches

Antirotation/lubrication Type And Quantity:

6 hole

Material:

Steel comp 4130

Material Specification:

Ems 638, 70210 mfr ref single material response

Surface Treatment:

Nickel

Surface Treatment Specification:

Mil-n-26074, cl 1 military specification single treatment response

Style Designator:

Solid, plain, no outside flanges, internal flange one end

Test Data Document:

81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0

Mil-std (military Standard):

Mil-n-26074 spec.