# NSN 3120-00-180-7029

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-180-7029

Over	all I	en	ath:
~~~	an L	-611	иит.

Between 0.2850 inches and 0.3000 inches

#### **Body Outside Diameter:**

Between 0.4381 inches and 0.4386 inches

#### **Body Inside Diameter:**

Between 0.3125 inches and 0.3140 inches

#### Flange Outside Diameter:

Between 0.5520 inches and 0.5720 inches

#### Flange Width:

Between 0.1200 inches and 0.1250 inches

#### **Corner Shape:**

Undercut left flange body corner

#### **Hardness Rating:**

34.0 rockwell c and 38.0 rockwell c

#### **Surface Finish:**

125.0 microinches intermediate layer

#### Material:

Steel comp e4340 or steel comp 4130

#### **Material Specification:**

Mil-s-5000 military specification 1st material response or mil-t-6736 com+4130 type 1, cond n military specification 2nd material response or mil-s-6758 condn military specification 3rd material response

#### **Surface Treatment:**

Cadmium and chromate

#### **Surface Treatment Specification:**

Qq-p-416 type 2, class2 federal specification single treatment response

# Style Designator:

Solid, external flange one end

# **Test Data Document:**

81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Shelf Life:

N/a

## **Unit Of Measure:**

\_

#### **Demilitarization:**

No

## Fiig:

A045a0

#### Mil-std (military Standard):

Mil-s-5000 spec.