NSN 3120-00-180-7141

Sleeve Bushing - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/3120-00-180-7141 |
|---|
| Overall Length: |
| Between 0.5250 inches and 0.5500 inches |
| Body Outside Diameter: |
| Between 1.0009 inches and 1.0014 inches |
| Body Inside Diameter: |
| Between 0.8760 inches and 0.8763 inches |
| Flange Outside Diameter: |
| Between 1.6000 inches and 1.6600 inches |
| Flange Width: |
| Between 0.0900 inches and 0.1100 inches |
| Corner Shape: |
| Undercut left flange body corner |
| Surface Finish: |
| 63.0 microinches right end surface of body |
| Material: |
| Cobalt alloy or steel |
| Material Specification: |
| Haynes no. 6, fscm 80798 mfr ref 1st material response or 300 cvm, fscm 87665 mfr ref 2nd material response |
| Surface Treatment: |
| Chromium left end surface of body and flange |
| Surface Treatment Specification: |
| Qq-c-320, cl 2 federal specification single treatment response left end surface of body and flange |
| Style Designator: |
| Solid, external flange one end |
| Test Data Document: |
| 81349-mil-i-6866 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A045a0 |

Mil-std (military Standard): Mil-c-8837 spec.