

View Online at <https://aerobasegroup.com/nsn/3120-00-185-3022>

Thread Class:

3b

Thread Direction:

Right-hand

Shank Style:

Internally threaded w/bead and wrench flats and inspection hole

Overall Length:

Between 2.1150 inches and 2.1350 inches

Bore Diameter:

Between 0.3745 inches and 0.3765 inches

Outer Member Outside Diameter:

Between 0.9900 inches and 1.0100 inches

Bore Center To Shank End Distance:

Between 1.6150 inches and 1.6350 inches

Outer Member Width:

Between 0.4010 inches and 0.4110 inches

Inner Member Width:

Between 0.4950 inches and 0.5000 inches

Shank Thread Length:

0.9370 inches

Inspection Hole Center To End Distance:

Between 0.4640 inches and 0.4740 inches

Shank Width Across Wrench Flats:

Between 0.5520 inches and 0.5720 inches

Static Radial Load Rating:

9589 pounds

Thread Diameter:

0.375 inches

Features Provided:

External lubrication fitting and screw plug closure fitting

Thready Qty Per Inch (tpi):

24

Lubrication Feature:

Groove internal inner member

Material:

Steel comp e52100 inner member

Material Specification:

66 federal standard single material response inner member

Surface Treatment:

Cadmium rod end body

Style Designator:

Ball type

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0