

View Online at <https://aerobasegroup.com/nsn/3120-00-187-9041>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Style:

Externally threaded

Overall Length:

Between 2.2975 inches and 2.3500 inches

Bore Diameter:

Between 0.2495 inches and 0.2500 inches

Outer Member Outside Diameter:

Between 0.8650 inches and 0.9100 inches

Bore Center To Shank End Distance:

Between 1.8650 inches and 1.8950 inches

Outer Member Width:

Between 0.3350 inches and 0.3500 inches

Inner Member Width:

Between 0.5880 inches and 0.5930 inches

Shank Thread Length:

Between 1.2500 inches and 1.3400 inches

Static Radial Load Rating:

5500 pounds

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

24

Hardness Rating:

45.0 rockwell c inner member

Special Features:

Std nas keyway in shank, 0.0005 in. Min 0.0015 in. Maximum diametral clearance

Material:

Stainless steel rod end body

Surface Treatment:

Chromium inner member

Style Designator:

Ball type

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A045a0