NSN 3120-00-191-2509

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-00-191-2509

Over	all I	en	ath:
~~~	an L	-611	иит.

Between 1.8856 inches and 1.8910 inches

**Body Outside Diameter:** 

Between 1.1360 inches and 1.1365 inches

**Body Inside Diameter:** 

Between 0.8747 inches and 0.8752 inches

**Corner Shape:** 

Round outside right corner

**Surface Finish:** 

63.0 microinches intermediate layer

**Special Features:** 

Id and od parallel and concentric within 0.001 in. Tir

Material:

Steel comp 4140 or steel comp 4130 or steel comp e4340 or steel comp 4340

## **Material Specification:**

Ams6381 assn standard 1st material response or mil-s-6758 cond d1 military specification 2nd material response or mil-s-5626 cond d1 military specification 3rd material response or mil-s-5000 military specification 4th material response or mil-t-6736 type 1 cond n military specification 5th material response

## **Surface Treatment:**

Cadmium right end surface of body

## **Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response right end surface of body

**Style Designator:** 

Solid, plain, no outside flanges

Shelf Life:

N/a

**Unit Of Measure:** 

_

Demilitarization:

No Fiig:

A045a0

Mil-std (military Standard):

Mil-s-6758 spec.