NSN 3120-00-191-2518

Sleeve Bushing - Page 1 of 1

Unit Of Measure:

Demilitarization:

Mil-s-6758 spec.

Mil-std (military Standard):

No Fiig: A045a0



View Online at https://aerobasegroup.com/nsn/3120-00-191-2518

| view Online at https://aerobasegroup.com/hsh/o120-00-131-2010 |
|--|
| Overall Length: |
| Between 1.8856 inches and 1.8910 inches |
| Body Outside Diameter: |
| Between 1.1460 inches and 1.1465 inches |
| Body Inside Diameter: |
| Between 0.8747 inches and 0.8752 inches |
| Corner Shape: |
| Round outside right corner |
| Surface Finish: |
| 63.0 microinches intermediate layer |
| Special Features: |
| Id and od parallel and concentric within 0.001 in. Tir |
| Material: |
| Steel comp 4140 or steel comp 4130 or steel comp e4340 or steel comp 4340 |
| Material Specification: |
| Ams 6381 assn standard 1st material response or mil-s-6758, condd1 military specification 2nd material response or mil-s-5626 cond d1 |
| military specification 3rd material response or mil-s-5000 cond c1 military specification 4th material response or mil-t-6736 type 1, cond n |
| military specification 5th material response |
| Surface Treatment: |
| Cadmium right end surface of body |
| Surface Treatment Specification: |
| Qq-p-416, type 2, cl 2 federal specification single treatment response right end surface of body |
| Style Designator: |
| Solid, plain, no outside flanges |
| Shelf Life: |
| N/a |